

**TABLE 2**  
**(340-35-030)**

**In-Use Road Vehicle Standards**

**Stationary Test**

| <u>Vehicle Type</u>  | <u>Model Year</u> | <u>Maximum<br/>Noise<br/>Level, dBA</u> | <u>Minimum Distance From<br/>Vehicle to Measurement<br/>Point</u> |
|--|-------------------|---|---|
| All vehicles described in ORS<br>481.205(2) (a)  | Before 1976       | 94                                      | 25 feet (7.6 meters)  |
|  | 1976 and after    | 91                                      | 25 feet (7.6 meters)  |
| All other trucks in excess of 8,000<br>pounds (3629 kg) GVWR                               | Before 1976       | 94                                      | 25 feet (7.6 meters)  |
|  | 1976-1981         | 91                                      | 25 feet (7.6 meters)  |
|  | After 1981        | 88                                      | 25 feet (7.6 meters)  |
| Motorcycles  | 1975 and Before   | 102                                     | 20 inches (1/2 meter)   |
|  | After 1975        | 99                                      | 20 inches (1/2 meter)   |
| Front-engine automobiles,<br>Light trucks and all other front-<br>engine road vehicles     | All               | 95                                      | 20 inches (1/2 meter)   |
| Rear-engine automobiles and<br>light trucks and mid-engine<br>automobiles and light trucks | All               | 97                                      | 20 inches (1/2 meter)   |
| Buses as defined under ORS<br>481.030  | Before 1976       | 94                                      | 25 feet (7.6 meters)  |
|  | 1976 and after    | 91                                      | 25 feet (7.6 meters)  |